




# 5P™

## POLYESTER SINGLE JACKET EPDM RUBBER LINED HOSE

Snap-tite's 5P™ is a medium pressure hose that is tough enough to meet most application requirements, while remaining economical for your budget. 5P™ is a polyester, single jacket style hose with an EPDM (Ethylene Propylene Diene Monomer) rubber liner that can handle most fluids, including some chemicals and petroleum-based products. It has a maximum operating pressure of 250 psi (1723 kPa) and can be treated with our optional Dura-Cote™ treatment for a higher level of abrasion resistance while preventing water-pickup.

### FEATURES

- Single jacket, polyester, EPDM rubber lined hose.
- Optional Dura-Cote™ protective treatment.
- Hose remains flexible at temperatures as low as -40°F (-40°C) and is resistant to ozone and oxidation.
- Available with aluminum or brass couplings.
- Designed for the following applications: General industrial and construction use; discharge hose in plant fire protection; wash down and maintenance.
- Made in USA to ISO-9001:2015 certified quality assurance system.
- 1½" and 2½" sizes are UL, ULC, and FM certified.




### HOSE COLORS



# 5P™

## POLYESTER SINGLE JACKET EPDM RUBBER LINED HOSE



### HOSE COLORS



TECHNICAL DATA & INFORMATION	
Model	5P™
Basic Construction	Polyester single jacket, EPDM rubber liner.
Application	Industrial
Colors:	Yellow, Red, White (uncoated)
Temperature Range	-40° F - 150° F

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE	TESTING PRESSURES (PSI)			WEIGHT (LBS/FT)	ABRASION RESISTANCE
	Working	Proof	Burst		
				Uncoupled	# of Taber Abrasion Cycles (H-22 wheel)
1-1/2"	250 psi	500 psi	750 psi	0.17	Exceeds UL19 Requirements
2"	250 psi	500 psi	750 psi	0.28	Exceeds UL19 Requirements
2-1/2"	250 psi	500 psi	750 psi	0.29	Exceeds UL19 Requirements
3"	250 psi	500 psi	750 psi	0.31	Exceeds UL19 Requirements

\*1-year warranty.

\*1-1/2" and 2-1/2" are UL/ULC/FM Certified

\*Potable water approved: No

\*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045