5P™


POLYESTER SINGLE JACKET EPDM RUBBER LINED HOSE

Snap-tite's 5P™ is a medium pressure hose that is tough enough to meet most application requirements, while remaining economical for your budget. 5P™ is a polyester, single jacket style hose with an EPDM (Ethylene Propylene Diene Monomer) rubber liner that can handle most fluids, including some chemicals and petroleum-based products. It has a maximum operating pressure of 250 psi (1723 kPa) and can be treated with our optional Dura-Cote™ treatment for a higher level of abrasion resistance while preventing water-pickup.

FEATURES

- Single jacket, polyester, EPDM rubber lined hose.
- Hose remains flexible at temperatures as low as -40°F (-40°C) and is resistant to ozone and oxidation.
- Available with aluminum or brass couplings.
- Designed for the following applications: General industrial and construction use; discharge hose in plant fire protection; wash down and maintenance.
- Made in USA to ISO-9001:2015 certified quality assurance system.
- 1½" and 2½" (Red and White) are UL, ULC, and FM certified.
- 1½" and 2½" (Yellow) are ULC/FM certified.





HOSE COLORS


Yellow	Red	White
		(uncoated)

UL ULC FM APPROVED USA MADE 1 YEAR WARRANTY

5P™

POLYESTER SINGLE JACKET EPDM RUBBER LINED HOSE





HOSE COLORS

Yellow | Red | White (uncoated)

TECHNICAL DATA & INFORMATION	
Model	5P™
Basic Construction	Polyester single jacket, EPDM rubber liner.
Application	Industrial
Colors:	Yellow, Red, White (uncoated)
Temperature Range	-40° F - 150° F

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE	**TESTING PRESSURES (PSI)**			**WEIGHT (LBS/FT)**	**ABRASION RESISTANCE**
	Working	Proof	Burst	Uncoupled	# of Taber Abrasion Cycles (H-22 wheel)
1-1/2″	250 psi	500 psi	750 psi	0.17	Exceeds UL19 Requirements
2-1/2″	250 psi	500 psi	750 psi	0.29	Exceeds UL19 Requirements

**1-year warranty.*
**Potable water approved: No*
**Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045*