


Snap-tite Hose's AgPro-XL™ leads the industry as the toughest, most reliable drag hose on the market. Purpose-built for high-volume liquid manure and sludge transfer, the AgPro-XL™ is engineered to thrive under the most demanding agricultural conditions. Its proprietary high-tenacity yarn construction delivers unmatched tensile strength, outperforming the competition by nearly 120%. This cutting-edge design not only maximizes durability but also significantly reduces downtime in the field. More than just a hose, AgPro-XL™ is a high-performance workhorse, engineered for power, built for endurance, and trusted for results.

#### **FEATURES**

- Hose withstands exposure to most hydro-carbons, gasolines, oils, alkalis, and grease.
- Hose remains flexible at temperatures as low as -60°F (-51°C) and as high as 180°F.
- Increased tensile strength for maximum service life and low operating costs.
- Ideal for the high-volume commercial pumper.
- Manufactured within our ISO-9001:2015 certified quality assurance system.





### **HOSE COLORS**














# **AGPRO-XLTM**

## THE INDUSTRY'S STRONGEST DRAG HOSE





### **HOSE COLORS**

White

TECHNICAL DATA & INFORMATION					
Model	AgPro-XL™				
Basic Construction	Polyurethane thru-the-weave extrusion				
Application	Agriculture				
Colors:	White				
Temperature Range	-60° F - 180° F				

TECHNICAL DATA & INFORMATION								
NOMINAL SIZE	WALL THICKNESS	TESTING PRESSURES (PSI)		WEIGHT (LBS/FT)	ABRASION RESISTANCE	TENSILE STRENGTH (LBS)		
		Working	Burst		# of Taber Abrasion Cycles (H-22 wheel)			
6"	PENDING							
7"	0.200"	275 psi	750 psi	2.05	750,000+	177,500		
7-1/4"	0.200"	275 psi	750 psi	2.07	750,000+	201,500		

<sup>\*1-</sup>year warranty.



<sup>\*</sup>Potable water approved: Yes

<sup>\*</sup>Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045