



FIRE ENGINE BOOSTER HOSE

RIGID, WOVEN ARAMID HOSE FOR REELS

The Fire Engine Booster hose is a robust and dependable choice for effective firefighting. Its multiple braid reinforcement provides durability, while the specially compounded Ethylene Propylene Diene Monomer (EPDM) outer cover offers excellent resistance to abrasion and weathering. Inside, the smooth black synthetic EPDM rubber enhances flexibility and ensures optimal flow and performance, making it ideal for tackling fires with confidence and reliability.

TEMPERATURE RANGE: -40F to 212F (-40C to 100C)

COUPLINGS: NH/NPSH Aluminum, Barway Brass, or Barway Chrome Brass

HOSE COLORS



TECHNICAL DATA & INFORMATION					
NOMINAL SIZE (INCHES)	BOWL SIZE (INCHES)	SERVICE PSI	PROOF PSI	BURST PSI	WEIGHT (LBS./50' COUPLED)
3/4"	1.25	800	1600	3200	16.5
1"	1.5	800	1600	3200	30.5
1-1/2"	2	220	440	660	39

*1-year warranty.

Warranty Conditions:

The manufacturer warrants the hose to be free from defects in materials and workmanship for a period of one year. This warranty shall provide for the repair or replacement of hose and couplings proven to have failed due to faulty material or workmanship.