




SNAP-TITE LD™

LIGHTWEIGHT EXTRUDED RUBBER HOSE

LD™ is a premium quality extruded thru-the-weave, nitrile rubber hose. It's easily coiled, non-kinking, high flow, lightweight hose that also resists abrasion, chemicals, and weathering by ozone.

FEATURES

- Extruded thru-the-weave, nitrile rubber fire hose. The reinforcement has circular woven, twill weave, and nylon fibers.
- Highly resistant to both conductive and radiant heat.
- Hose remains flexible at temperatures as low as -40°F (-40°C) and is resistant to ozone, oxidation, and most chemicals and petrochemicals.
- Designed for the following applications: General industrial and construction use; discharge hose in plant fire protection; wash down and maintenance.
- Maintenance free, no drying required, and is easily cleaned.
- Made in USA to ISO-9001:2015 certified quality assurance system.



HOSE COLORS



ATTACK



USA MADE



SNAP-TITE LD™

LIGHTWEIGHT EXTRUDED RUBBER HOSE



HOSE COLORS



TECHNICAL DATA & INFORMATION	
Model	LD™
Basic Construction	Nitrile rubber thru-the-weave with nylon reinforcing jacket.
Application	Attack
Colors:	Yellow, Red, Blue
Temperature Range	-40° F - 200° F

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE	TESTING PRESSURES (PSI)			WEIGHT (LBS/FT)	ABRASION RESISTANCE
	Working	Proof	Burst	Uncoupled	# of Taber Abrasion Cycles (H-22 wheel)
1-3/4"	300 psi	600 psi	900 psi	0.22	5,500
2-1/2"	300 psi	600 psi	900 psi	0.4	8,500

*1-year warranty.

*2-1/2" is UL/ULC Certified

*LD15 available upon request. Minimum order required.

*Potable water approved: No

*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045