




UTX™ LDH

PREMIUM HOSE. OUTSTANDING VALUE.

UTX™ is a tough lightweight extruded thru-the-weave hose. Its polyurethane material provides greater resistance to punctures and abrasion, while the thru-the-weave liner guarantees a lifetime warranty against delamination. UTX™ is compact and durable while providing higher resistance to oils, chemicals, and ozone.

FEATURES

- Typical rubber extruded hose can vary in thickness, becoming bulky and heavy. UTX™ incorporates a circular woven polyester jacket that is completely encapsulated by an extruded thru-the-weave polyurethane cover and liner that provides abrasion and puncture resistance while remaining light and service worthy.
- UTX™ weighs 20% less than conventional rubber supply hose.
- Extruded thru-the-weave polyurethane construction and ultra-smooth liner minimize friction loss.
- Engineered to deliver more flow and more efficient packability.
- Remains flexible to -50°F (-46°C).
- Resists ozone, oxidation, and most chemical/petroleum products.
- Made in USA to ISO-9001:2015 certified quality management system.




HOSE COLORS



Snaptitehose.com | 814.438.7616

UTX™ LDH

PREMIUM HOSE. OUTSTANDING VALUE.



HOSE COLORS



TECHNICAL DATA & INFORMATION

Model	UTX™ LDH
Basic Construction	Polurethane thru-the-weave with polyester inner reinforcement.
Application	Supply
Colors:	Yellow, Hi-Viz Green, Blaze Orange, Yellow
Temperature Range	-50° F - 160° F

TECHNICAL DATA & INFORMATION

NOMINAL SIZE	TESTING PRESSURES (PSI)			WEIGHT (LBS/FT)	ABRASION RESISTANCE
	Working	Proof	Burst		
4"	200 psi	400 psi	600 psi	0.5	# of Taber Abrasion Cycles (H-22 wheel) 100,000+
5"	200 psi	400 psi	600 psi	0.73	100,000+

*1-year warranty.

*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045