

UTX™ LDH

PREMIUM HOSE. OUTSTANDING VALUE.

UTX™ LDH gives fire departments that extra edge in flow and support - all in a high-visibility, lightweight supply line. A tough polyurethane outer cover combines with an exclusive thru-the-weave polyurethane liner to offer greater resistance to punctures and abrasion. But it doesn't stop there. UTX™ is compact, taking up less room in the hose bed, and durable - with higher resistance to oils, chemicals, and ozone. Snag proof and kink resistant, UTX™ will not mildew or rot and is guaranteed for life to never delaminate.

FEATURES

- Typical rubber extruded fire hose can vary in thickness, becoming bulky and heavy. UTX™ LDH incorporates a circular woven polyester jacket that is completely encapsulated by an extruded thru-the-weave polyurethane cover and liner that provides abrasion and puncture resistance while remaining light and service worthy.
- UTX™ weighs 20% less than conventional rubber supply hose.
- Extruded thru-the-weave polyurethane construction and ultra-smooth liner minimize friction loss.
- Engineered to deliver more flow and more efficient packability.
- Remains flexible to -50°F (-46°C).
- Resists ozone, oxidation, and most chemical/petroleum products.
- Manufactured in accordance with NFPA 1960 Standard, latest edition.
- Made in USA to ISO 9001:2015 certified quality management system.



HOSE COLORS

Red	Hi-Viz Green	Blaze Orange	Yellow

USA MADE

LIFETIME DELAMINATION WARRANTY | 2 YEARS WARRANTY | 10 YEAR WARRANTY

UTX™ LDH

PREMIUM HOSE. OUTSTANDING VALUE.



HOSE COLORS

Red | Hi-Viz Green | Blaze Orange | Yellow

TECHNICAL DATA & INFORMATION	
Model	UTX™ LDH
Basic Construction	Polyurethane thru-the-weave with polyester inner reinforcement.
Application	Supply
Colors:	Red, Hi-Viz Green, Blaze Orange, Yellow
Temperature Range	-50° F - 160° F
Testing Pressures:	
Service	200 psi
Proof	400 psi
Burst	600 psi

UTX™ LDH

PREMIUM HOSE. OUTSTANDING VALUE.

TECHNICAL DATA & INFORMATION										
NOMINAL SIZE	INTERNAL/OUTSIDE DIAMETER				WEIGHT					
	Dry ID	Charged ID at 50 psi	Charged ID at 150 psi	Charged OD at 150 psi	Water Pickup Weight*	Dry (lbs./100′ coupled)	Charged at 50 psi (lbs./50′ coupled)	# of Gallons/50′	Charged at 150 psi (lbs./50′ coupled)	# of Gallons/50′
4″	4.05″	Not applicable per NFPA			0 LBS	70 LBS	Not applicable per NFPA			
5″	5.05″	Not applicable per NFPA			0 LBS	93 LBS	Not applicable per NFPA			

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE	DOORWAY KINK	ABRASION RESISTANCE	PACKABILITY		
		# of Taber Abrasion Cycles (H-22 wheel)	Flat Width	Edge Thickness	180° Bend Thickness
4″	Not applicable per NFPA	100,000+	6.50″	.75″	1.60″
5″	Not applicable per NFPA	100,000+	7.75″	.75″	1.60″

**10-year warranty, 2-year all hazard warranty.*
**MIL Std 24606 used for water pickup weight.*
**Potable water approved: Yes*
**Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045*