

The logo for Snap-tite HOSE is located in the top left corner. It features the brand name "Snap-tite" in a white, cursive script font, with "HOSE" in a smaller, white, sans-serif font below it. A small icon of a hose fitting is positioned between the two words. A trademark symbol (TM) is located at the end of the word "HOSE".

Snap-tite
HOSE™

The background of the entire page is a photograph of a vast agricultural field, likely a cornfield, with rows of crops stretching towards the horizon. The scene is captured at sunset, with a bright sun low on the horizon, casting a warm, golden glow over the landscape. The sky is filled with dramatic, dark clouds illuminated from below by the setting sun. The overall mood is serene and productive.

AGRICULTURAL
QUICK HOSE
GUIDE



PRODUCT OFFERINGS

ICON GUIDE:



ISO 9001: 2015 CERTIFIED QUALITY MANAGEMENT SYSTEM



AgFlo™


- Heavy-duty hose made from 100% high tenacity yarn with an extruded thru-the-weave polyurethane inner liner.
- Designed pressure: 200 psi.
- AgFlo™ has the highest burst pressure rating and the thickest outer cover in the industry.
- Hose withstands exposure to hydro-carbons, gasolines, oils, alkali, and grease.
- The polyurethane lining materials meets NSF/ANSI Standard 61 for drinking water.
- Application: Drag Hose

SIZES: 5", 5-1/2", 6"

COLORS:  

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

- 814-438-7616
- customerservice@snaptitehose.com
- snaptitehose.com



PRODUCT OFFERINGS



IR™

- Constructed of 100% high tenacity yarn with an extruded thru-the-weave polyurethane inner liner.
- Designed pressure: 200 psi.
- Built for fast deployment and retrieval with five times more abrasion resistance than conventional rubber hose.
- Hose withstands exposure to hydro-carbons, gasolines, oils, alkali, and grease.
- The polyurethane lining materials meets NSF/ANSI Standard 61 for drinking water.
- Application: Irrigation Hose

SIZES: 3", 4", 4-1/2"

COLORS:



XLF™


- The XLF™ inner jacket is designed with 100% high tenacity polyester yarn and extruded thru-the-weave polyurethane.
- Designed pressure: 200 - 300 psi.
- Multi-purpose large diameter hose for oil/gas, water transfer, dewatering refineries for tank fire suppression, nuclear, agriculture, military, and water/sewer bypass during construction.
- The polyurethane lining materials meets NSF/ANSI Standard 61 for drinking water.
- Application: Agriculture, Industrial, Military

SIZES: 7-1/4", 8", 10"

COLORS:

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

- 814-438-7616
- customerservice@snaptitehose.com
- snaptitehose.com

NOTES:

