

The image shows two firefighters in a dynamic scene. One firefighter is kneeling in the foreground, wearing a light-colored jacket and a dark helmet. The other firefighter is standing behind him, wearing a grey t-shirt with 'Snap-Tite' and 'INNOVATIVE' printed on the back, tan pants, and a dark helmet. He is holding a tool, possibly a nozzle, and there are sparks or embers floating in the air around them. The background is dark and smoky. In the top right corner, the 'Snap-Tite HOSE' logo is visible, featuring the brand name in a stylized script and 'HOSE' in a bold, sans-serif font with a small icon of a hose connector.

Snap-Tite
HOSE™

MUNICIPAL QUICK HOSE GUIDE

ICON GUIDE:



AMERICAN MADE

ISO 9001: 2015 CERTIFIED QUALITY MANAGEMENT SYSTEM



1-YEAR WARRANTY



2-YEAR ALL HAZARD WARRANTY



3-YEAR ALL HAZARD WARRANTY



10-YEAR WARRANTY



LIFETIME WARRANTY AGAINST DELAMINATION



KLEAN HOSE



FORESTRY HOSE



ATTACK HOSE



SUPPLY LINE HOSE



SOFT SUCTION HOSE



HIGH-RISE HOSE



PRODUCT OFFERINGS



WARRIOR™ FW & FWN



- Proprietary para aramid outer jacket material with a thru-the-weave nitrile rubber liner construction.
- Recommended flow pressure: 50 - 100 psi.
- 60 minutes of radiant testing at 30 kw/m² of heat flux without failure.
- More than three times the abrasion resistance of any current hose on the market: 91,000+ taber cycles.
- An attack line designed with a 1.77" (FWN) or 1.88" (FW) ID waterway.
- UL/ULC certified
- UL-19 heat resistance type: Type 1
- Application: Attack, Low PSI, CAFS

SIZES: 1-3/4", 2-1/2"

COLORS: NATURAL



GLADIATOR™ FG & FGN



- Premium quality, outside jacket with a nitrile rubber thru-the-weave inner liner construction.
- Recommended flow pressure: 50 - 100 psi.
- Suitable for CAFS and foam concentrates.
- FGN - Designed for a 7/8" Smooth Tip, to be flowed at 160 GPM flow rate.
- An attack line designed with a 1.77" (FGN) or 1.88" (FG) ID waterway.
- UL-19 heat resistance type: Type 2 (FG 1-3/4", 2-1/2")
- Application: Attack, Low PSI, CAFS

SIZES: 1-3/4", 2", 2-1/2"

COLORS: COATED



SUPREME™ II & LDH



- Premium polyester double jacketed fire hose with an onyx nitrile rubber thru-the-weave liner.
- Recommended flow pressure: 50 - 100 psi.
- Features a smooth and enhanced waterway for better flow and less kinking.
- Suitable for CAFS and foam concentrates.
- UL-19 heat resistance type: Type 2
- Supreme™ II Application: Attack, Low PSI, CAFS
- Supreme™ II LDH Application: Supply


SIZES: 1-1/2", 1-3/4", 2", 2-1/2", 3", 4", 5"

COLORS: COATED

*For UL/ULC information, visit our website.

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

- 📞 814-438-7616
- ✉️ customerservice@snaptitehose.com
- ✉️ orders@snaptitehose.com
- 🌐 snaptitehose.com



PRODUCT OFFERINGS

CONQUEST™ & LDH



- Patented double jacketed fire hose made from 100% high tensile strength polyester outer jacket with extruded thru-the-weave polyurethane inner hose.
- Recommended flow pressure: 75 - 100 psi.
- Outstanding flow and low friction loss.
- Suitable for CAFS and foam concentrates.
- UL-19 heat resistance type: Type 2 (1-3/4", 2-1/2")
- Conquest™ Application: Attack, High Rise, CAFS
- Conquest™ LDH Application: Supply

SIZES: 1-3/4", 2", 2-1/2", 3", 4", 5", 6"

COLORS:      

8D™



- Double jacketed EPDM rubber lined hose made from 100% high tensile strength polyester yarn.
- Recommended flow pressure: 100 psi.
- Highly resistant to ozone and oxidation.
- UL-19 heat resistance type: Type 2 (1-3/4", 2-1/2")
- 1-3/4" and 2-1/2" are ULC Certified
- Application: Attack

SIZES: 1-1/2", 1-3/4", 2-1/2", 3"

COLORS:      

5P™



- Single jacket, polyester, EPDM rubber lined hose.
- Resistant to most petrochemicals.
- Available with aluminum or brass couplings.
- UL-19 heat resistance type: Type 3 (1-1/2", 2-1/2")
- 1-1/2" and 2-1/2" are UL/ULC/FM Certified
- Applications: Industrial

SIZES: 1-1/2", 2", 2-1/2"


COLORS:   



*For UL/ULC information, visit our website.

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

-  814-438-7616
-  customerservice@snaptitehose.com
-  orders@snaptitehose.com
-  snaptitehose.com



PRODUCT OFFERINGS

LD™




- Extruded thru-the-weave, nitrile rubber fire hose with reinforcement via circular woven, polyester, and nylon fibers.
- Highly resistant to both conductive and radiant heat.
- Lightweight and kink resistant at low pressures makes this hose superior for high rise firefighting.
- UL-19 heat resistance type: Type 3 (2-1/2")
- 2-1/2" is UL/ULC Certified
- Application: Attack, High Rise

SIZES: 1-3/4", 2-1/2"

COLORS:   

HFX™



- Extruded thru-the-weave, nitrile rubber construction with a polyester and nylon reinforcing jacket.
- Construction creates a concentric, flexible, and maneuverable hose that is also easy to pack.
- Ribs on the cover surface greatly increase abrasion resistance and help provide a long service life.
- HFX™: UL-19 Type 2 heat resistance (1-3/4"), Type 3 heat resistance (1-1/2", 2-1/2").
- HFX™ Application: Attack
- 1-1/2", 1-3/4", and 2-1/2" are UL/ULC Certified. 2" is ULC only.
- HFX™ LDH Application: Supply
- 4" and 5" are UL/ULC Certified

SIZES: 1", 1-1/2", 1-3/4", 2", 2-1/2", 3", 4", 5"

COLORS:  

UTX™



- Woven, polyester jacket construction with an extruded thru-the-weave polyurethane cover and liner.
- UTX™ is the most compact, flexible, and lightest LDH on the market.
- Resists ozone, oxidation, and most chemical/petroleum products.
- Ergonomically designed and constructed to be up to 30 lbs (per 100 ft) lighter than conventional LDH.
- Application: Supply


SIZES: 4", 5"

COLORS:    

*For UL/ULC information, visit our website.

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

- 📞 814-438-7616
- ✉️ customerservice@snaptitehose.com
- ✉️ orders@snaptitehose.com
- 🌐 snaptitehose.com



PRODUCT OFFERINGS

TPX™



- 3-ply nitrile rubber cover/liner with polyester inner jacket.
- Unique 3-ply design affords incredible strength but with a lightweight profile, making it easy to manage on the fireground and virtually eliminating snaking.
- Lays flat, requiring less hose bed space than typical extruded hose.
- Application: Supply
- 4" and 5" are UL/ULC Certified

SIZES: 4", 5", 6", 8"

COLORS:    



BLAZELINE™



- Polyester single jacket hose.
- BlazeLine™ 7 is designed for traditional Type I specifications.
- BlazeLine™ 8 meets the Type II specification and is mildew-resistant.
- Application: Forestry

SIZES: 1", 1-1/2"


COLORS:  
BlazeLine™ 8 BlazeLine™ 7



*For UL/ULC information, visit our website.

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US


- 📞 814-438-7616
- ✉️ customerservice@snaptitehose.com
- ✉️ orders@snaptitehose.com
- 🌐 snaptitehose.com

NOTES:

**For UL/ULC information, visit our website.*

All Snap-tite Hose products are manufactured in accordance with NFPA 1960 standard, latest edition within our ISO-9001:2015 certified quality assurance system.

SCAN ME TO LEARN MORE



CONTACT US

-  814-438-7616
-  customerservice@snaptitehose.com
-  orders@snaptitehose.com
-  snaptitehose.com

