




HFX™ LDH

EXTRUDED NITRILE RUBBER SUPPLY HOSE

HFX™ is a nitrile thru-the-weave, rubber covered fire hose that utilizes polyester and nylon 6.6 yarn in the reinforcing jacket. Under pressure, the polyester keeps the hose from snaking, while the nylon allows for controlled dilation, reducing friction loss, and generating higher flow rates. Our special rubber compound provides a tough cover that resists heat, abrasion, snags, and hot embers. The interlocking matrix also means no adhesives are used and there is a permanent bond to all the warp and USA MADE weft yarns. The Snap-tite HFX™ is highly resistant to both conductive and radiant heat.

FEATURES

- Extruded thru-the-weave, nitrile rubber fire hose. The reinforcement is made with a blend of circular woven, twill weave, polyester and, nylon fibers.
- The ribs on the cover surface greatly increase abrasion resistance and help provide a long service life.
- Remains flexible at temperatures as low as -40°F (-40°C) and is resistant to ozone, oxidation and most chemicals and petrochemicals.
- Suitable for supply, soft sleeve suction, and relay applications.
- Extruded nitrile rubber thru-the-weave construction provides a flexible, easy to maneuver hose that is easy to pack.
- Manufactured in accordance with NFPA 1960 Standard, latest edition within our ISO-9001:2015 certified quality assurance system.



USA MADE



HOSE COLORS


Yellow

Red



HFX™ LDH

EXTRUDED NITRILE RUBBER SUPPLY HOSE



HOSE COLORS

Yellow

Red



TECHNICAL DATA & INFORMATION

Model	HFX™ LDH
Basic Construction	Nitrile rubber thru-the-weave with polyester and nylon reinforcing jacket.
Application	Supply
Colors:	Yellow, Red
Temperature Range	-40° F - 200° F

TESTING PRESSURES

Nominal Size	Service	Proof	Burst
4"	250 psi	500 psi	750 psi
5"	225 psi	450 psi	675 psi
6"	225 psi	450 psi	675 psi

HFX™ LDH

EXTRUDED NITRILE RUBBER SUPPLY HOSE

TECHNICAL DATA & INFORMATION

NOMINAL SIZE	INTERNAL/OUTSIDE DIAMETER				WEIGHT					
	Dry ID	Charged ID at 50 psi	Charged ID at 150 psi	Charged OD at 150 psi	Water Pickup Weight*	Dry (lbs./100' coupled)	Charged at 50 psi (lbs./50' coupled)	# of Gallons/50'	Charged at 150 psi (lbs./50' coupled)	# of Gallons/50'
4"	4.19"	-	-	-	-	98	-	-	-	-
5"	5.09"	-	-	-	-	111	-	-	-	-
6"	6.15"	-	-	-	-	160	-	-	-	-

TECHNICAL DATA & INFORMATION

NOMINAL SIZE	DOORWAY KINK	ABRASION RESISTANCE	HEAT RESISTANT TESTING (CONDUCTIVE)		HEAT RESISTANT TESTING (RADIANT)		PACKABILITY		
			Average Time to 20 psi Drop	Average GPM Loss	Average Time to 20 psi Drop	Average GPM Loss	Flat Width	Edge Thickness	180° Bend Thickness
4"	-	# of Taber Abrasion Cycles (H-22 wheel) 23,500	-	-	-	-	6.75"	.60"	1.60"
5"	-	20,800	-	-	-	-	8.20"	.60"	1.70"
6"	-	20,800	-	-	-	-	9.75"	.65"	1.80"

*1-year warranty.

*MIL Std 24606 used for water pickup weight.

*4" and 5" are UL/ULC Certified

*Potable water approved: No

*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045