



1.5" SUPREME™ II

**SMALL DIAMETER.
BIG PERFORMANCE.**

When you're advancing a line, control and consistency matter. The 1.5" Supreme™ II attack hose is designed for superior handling, dependable flow, and reduced fatigue on the fireground. Built to perform at a recommended operating rate of **125 GPM at 75 PSI**, this lightweight hose provides smooth water delivery with minimal kink and friction loss, helping crews move faster and stay in control from door to knockdown. Rugged, flexible, and built to last, the Supreme™ II is the compact attack line that doesn't compromise on performance.

FEATURES

- **Optimized Flow Performance** – Manufacturer-rated for 125 GPM @ 75 PSI for balanced stream quality and nozzle control.
- **Lightweight Handling** – Reduces fatigue during long advances and rapid deployments.
- **Durable Jacket Construction** – Resists abrasion, heat, and chemical exposure.
- **Smooth Waterway** – Delivers predictable, efficient flow with minimal friction loss.
- **Kink-Resistant Flexibility** – Maintains flow through bends and tight corners.
- **Quick, Reliable Coupling Options** – NH, Storz, or custom-fit couplings available.
- **Easy to Clean & Maintain** – Resists contamination and retains flexibility after repeated use.


PERFORMANCE HIGHLIGHTS

- Designed for smooth, efficient water flow at 125 GPM @ 75 PSI.
- Maintains flexibility and flow even under pressure.
- Lightweight yet rugged enough for aggressive interior or exterior attack.
- Ideal for departments standardizing on high-efficiency, low-pressure attack lines.

CARE & MAINTENANCE

Rinse and dry after exposure to dirt, debris, or chemicals. Store coiled in a cool, dry area away from UV exposure. Inspect regularly for jacket integrity and coupling condition. Test per NFPA 1962 or your department's maintenance schedule.

ORDERING INFORMATION



1.5" SUPREME™ II

SMALL DIAMETER. BIG PERFORMANCE.

TECHNICAL DATA & INFORMATION	
Model	1.5" Supreme™ II
Basic Construction	Polyester outer/inner jacket, extruded thru-the-weave onyx nitrile liner.
Application	Attack, Low PSI, CAFS
Colors:	Yellow, Red, Blue, Orange, Green, White (coated), White (uncoated)
Stripe Colors:	Yellow, Red, Blue, Black, Green
Temperature Range	-40° F - 200° F
Testing Pressures:	
Service	400 psi
Proof	800 psi
Burst	1200 psi

TECHNICAL DATA & INFORMATION										
NOMINAL SIZE	INTERNAL/OUTSIDE DIAMETER				WEIGHT					
	Dry ID	Charged ID at 50 psi	Charged ID at 150 psi	Charged OD at 150 psi	Water Pickup Weight*	Dry (lbs./50' coupled)	Charged at 50 psi (lbs./50' coupled)	# of Gallons/50'	Charged at 150 psi (lbs./50' coupled)	# of Gallons/50'
1-1/2"	1.53"	1.550"	1.596"	1.852"	2.9 LBS	15.6	56	4.9	58.7	5.1

TECHNICAL DATA & INFORMATION					
NOMINAL SIZE	DOORWAY KINK	ABRASION RESISTANCE	PACKABILITY		
		# of Taber Abrasion Cycles (H-22 wheel)	Flat Width (MM)	Edge Thickness (IN)	180° Bend Thickness (IN)
1-1/2"	18" / 50psi	37,000+	68.8	0.46"	0.84"

TECHNICAL DATA & INFORMATION										
NOMINAL SIZE	RADIANT HEAT TEST RESULTS					CONDUCTIVE HEAT TEST RESULTS				
	Radiant Heat Exposure	Exposure Duration*	Average Leakage Rate at 150 psi	Max Leakage Rate at 150 psi	UL 19 Heat Resistance Type	Conductive Heat Exposure	Exposure Duration*	Average Leakage Rate at 150 psi	Max Leakage Rate at 150 psi	UL 19 Heat Resistance Type
1-1/2"	30 kw/m2	2M / 38S (Red)	5 GPM	5 GPM	Type 2	Steel block at 752°F	21.92S (Red)	5 GPM	5 GPM	Type 2

*The results from the radiant heat test are based on controlled laboratory testing and do not represent actual conditions encountered during firefighting. These results are intended to be used as a baseline for hose comparison purposes only and are not indicative of specific field performance. Several factors can influence hose performance relative to radiant heat, please see Guidance for Lined Fire Hose and Hose Assemblies, UL 19G for further information on these results.

*10-year warranty, 2-year all hazard warranty.

*MIL Std 24606 used for water pickup weight.

*Potable water approved: No

*Quality Management System Certification: ISO 9001:2015 Registration # 11-R1045

